



EUROPEAN PATENT APPLICATION

Application number: 92107052.0

Int. Cl.<sup>5</sup>: **G01N 35/02, G01N 33/48, G06K 7/10, G05B 15/00**

Date of filing: 24.04.92

Priority: 26.04.91 JP 96721/91

Date of publication of application:  
 28.10.92 Bulletin 92/44

Designated Contracting States:  
 DE FR GB

Applicant: **HITACHI, LTD.**  
 6, Kanda Surugadai 4-chome  
 Chiyoda-ku, Tokyo 101(JP)

Inventor: **Takahashi, Katsuaki**  
 2031-813, Tsuda  
 Katsuta-shi(JP)

Inventor: **Mitsumaki, Hiroshi**  
 2819-17, Senbacho

**Mito-shi(JP)**


Inventor: **Yotsugi, Takehiko**  
 Nakagawa Apato E-104, 1030, Ichige  
 Katsuta-shi(JP)

Representative: **Altenburg, Udo, Dipl.-Phys. et al**  
**Patent- und Rechtsanwälte**  
**Bardehle-Pagenberg-Dost-Altenburg**  
**Frohwitter-Geissler & Partner Postfach 86 06 20**  
**W-8000 München 86(DE)**

Automatic analyzing apparatus capable of reading container data and method of handling reagents employed in the same.

When a lid of a reagent container housing unit is closed, an opening/closing detector outputs a signal. A control unit gives an instruction of moving a row of reagent containers and a bar code reader relative to each other to a driving unit and an instruction of starting the data reading operation to the bar code reader. When the lid of the container housing unit is closed, all the data which have been already read are reset. An automatic analyzing apparatus can select, in place of the data reading mode, the liquid level detection mode in which a level of the liquid in each of the reagent containers is detected.

FIG. 2



## BACKGROUND OF THE INVENTION

### Industrial Field of the Invention:

The present invention relates to an automatic analyzing apparatus and a method of handling reagents employed in the automatic analyzing apparatus. More particularly, the present invention pertains to an automatic analyzing apparatus and a reagent handling method which are suitable for use when data on a liquid contained in a container, which is inscribed on the container, is read.

### Description of the Related Art:

In an automatic analyzing apparatus in which an organism sample, such as blood or urine, is mixed with reagents in a reaction container and in which the reaction liquid is measured to perform analysis about the inspection items of the sample, reagents are supplied to the reaction container from a reagent container by a reagent delivery device.

The method of adding reagents into the reaction containers correspondingly to the inspection items has been described in, for example, U.S. Patent Publication No. 4,451,433. In this method, the reagents are supplied from the reagent containers fixedly loaded in a reagent container housing unit by a pipetting mechanism. Japanese Patent Publication No. 59-22905 discloses the method in which a desired reagent container is located to a reagent picking position by rotating a turn table provided in the reagent container accommodating portion, and a reagent is pipetted from that reagent container by a pipette mechanism. Japanese Patent Unexamined Publication No. 61-68562 discloses the method of supplying a reagent from a reagent container fixedly provided in a reagent container accommodating portion by a disperser mechanism through a flow passage.

In an analyzing apparatus in which a large number of containers are handled, each of the containers has identification data, such as a bar code, and the data of each of the containers is read correspondingly to the position of that container. Such a technique has been described in, for example, Japanese Patent Unexamined Publication Nos. 62-95464, 61-68562 and 59-226865. Among these techniques, Japanese Patent Unexamined Publication No. 59-226865 implies the reading of the data on all of the reagent containers before reagents are delivered to reaction containers.

Among the aforementioned conventional techniques, only Japanese Patent Unexamined Publication No. 59-226865 has proposed the use of reagent containers with a bar code provided thereon. In an automatic analyzing apparatus to which

the above-mentioned technique has been applied, when the operator holds the reagent containers in the container accommodation portion, he/she may forget to give the instruction to the data reading sensor. In that case, the reagent data input before the containers are replaced remains unchanged, and the operation of the analyzing apparatus will be troubled. Furthermore, when incorrect reagent containers are erroneously loaded in the container accommodating portion by the operator, the analyzing apparatus cannot respond to it.

## SUMMARY OF THE INVENTION

It is an object of the present invention to provide an automatic analyzing apparatus which is capable of reliably grasping data on the liquid in a container loaded in a container housing unit.

It is another object of the present invention to provide an automatic analyzing apparatus and a reagent handling method which are capable of preventing troubles which would occur when the analysis operation proceeds with reagents inadequate to the reactions for objective inspection items loaded in a reagent accommodating portion.

It is another object of the present invention to provide an automatic analyzing apparatus and a reagent handling method which can inform the operator that the reagents inadequate to the reactions for the objective inspection items are loaded in a reagent accommodating portion.

To achieve the above objects, the present invention provides an automatic analyzing apparatus which is designed to automatically read the data attached to a container loaded in a container housing unit without troubling the operator. The container data reading operation by a reading device is initiated by a detection signal obtained when an opening of the container housing unit is closed by a lid.

To achieve the above objects, the present invention further provides an automatic analyzing apparatus which is designed to prevent troubles of the analyzing apparatus which would occur when inadequate reagent containers are provided in a reagent accommodating portion. The types of reagents which are to be loaded in the reagent container accommodating portion are registered beforehand. When the reagent container whose data is read by the reading device does not correspond to the registered ones, the reagent delivery device is not activated.

Generally, the operator of the automatic analyzing apparatus loads reagent containers in the reagent container housing unit in a preparation stage before the analysis operation by the analyzing apparatus begins. After the operator has loaded necessary reagent containers or replaced the

reagent containers with new ones, he/she closes the opening of the housing unit with a lid. Closing of the lid produces a detection signal which initiates the reading operation of the data reading device. Thus, the reading operation can be reliably started without troubling the operator after the reagent containers have been loaded.

In an automatic analyzing apparatus in which analysis is performed on multiple inspection items, many types of reagents are used, or two, three or four types of reagents may be used for one analysis item. Generally, the first and second reagents regarding the same analysis item are loaded separately, for example, on different rows, because they are added to the reaction container at different times. However, the operator may misplace the first reagent at the position of the second reagent and vice versa.

Misplacement of the first and second reagents can be checked by registering the types of reagents that can be loaded in the reagent accommodating portion beforehand, by reading the data on the reagent containers loaded in the accommodating portion and then by performing collation on these two data items. When inadequate reagents are loaded, at least the reagent delivery device is locked to prevent troubles. Furthermore, since the operation of the analyzing apparatus is not initiated, the operator can notice the abnormality before the continuous analysis operation begins. Preferably, inadequate reagents are displayed on a screen. Thus, the analyzing apparatus can recommend the operator replacement of the inadequate reagents with correct ones. After the inadequate reagents have been replaced, the reagent delivery device is unlocked, and the automatic analyzing apparatus initiates continuous analysis operation.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a cross-sectional view of a reagent container housing unit in an automatic analyzing apparatus shown in Fig. 2;

Fig. 2 is a schematic view of an embodiment of an automatic analyzing apparatus according to the present invention;

Fig. 3 is a schematic view of another embodiment of an automatic analyzing apparatus according to the present invention;

Fig. 4 is a cross-sectional view of a reagent container housing unit of the embodiment shown in Fig. 3.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

A first embodiment of the present invention will be described below with reference to Figs. 1 and 2.

An automatic analyzing apparatus analyzes blood or urine specimens utilizing biochemical or immune reaction. Fig. 2 outlines the entire layout of an analyzing apparatus. Fig. 1 illustrates the structure of a reagent container housing unit.

In the analyzing apparatus shown in Fig. 2, a large number of reaction containers 15 are disposed on a reaction disk 50 which is intermittently driven by a driving unit 53 such that each of the reaction containers 15 crosses an optical path of a photometer 18. The reaction containers 15 are correspondent to the analysis items on which reaction should take place. The driving unit 52 is controlled by a control unit 11 through an interface 61.

Sample containers 52 are disposed on a sample disk 13 rotated by a driving unit 54 in such a manner that they can be stopped at a sample picking position one by one. The blood serum contained in each of the sample containers 52 is delivered by a sample pipetting mechanism 14 into the same number of reaction containers 15 as the number of required analysis items. First and second reagents are added to each of the reaction containers 15 from two reagent supply systems at predetermined times. Third and fourth reagents may be added in addition to the first and second reagents, depending on the analysis items.

The photometer 18 measures the liquid in the reaction container in which reaction between the sample and the reagents has completed. An analog signal obtained by photometry is converted into a digital signal by an analog/digital converter 55, and the converted signal is input to an operating unit 60 which operates the concentration or active value for each of the analysis items. The results of the operations are output by a printer 64. When necessary, they are displayed by a display unit 63, such as a CRT.

The analysis apparatus shown in Fig. 2 has at least two reagent supply systems. In the first reagent supply system, a large number of first reagent containers 1A are provided on a reagent disk 16A. A desired reagent is delivered to the corresponding reaction container 15 on the reaction disk at a desired time by a first reagent pipetting mechanism 17A. In the second reagent supply system, when a desired one in a large number of second reagent containers 1B provided on a reagent disk 16B is located at a reagent picking position, the reagent in that desired container is delivered to the corresponding reaction container 15 by a second reagent pipetting mechanism 17B.

Each of the reagent containers 1A and 1B has data on the liquid contained therein inscribed on the outer wall thereof. Examples of the data include the corresponding analysis item, the type of the reagent, the size of the reagent container, manufacturer's lot number and so on. Inscription may be

made by digits, symbols or bar codes. In this embodiment, bar code notation is used. Although a bar code may be directly printed on the outer wall of each of the containers, a bar code label is generally pasted on a predetermined position of the container.

Each of the reagent disks 16A and 16B is rotated by a corresponding driving unit 8 such that a desired reagent container 1A or 1B is located at the reagent picking position. While the disk 16A or 16B is at a stop, a reagent delivery system picks a predetermined amount of reagent. The reagent delivery system has the reagent pipetting mechanisms 17A and 17B and corresponding delivery mechanism driving units 56 which are controlled by a control unit 11. Each of the reagent pipetting mechanisms 17A and 17B has a pipette probe having a liquid level sensor. After the picked reagent is discharged into the corresponding reaction container 15, each of the pipette probes is washed by a corresponding pipette washing unit. A stirring mechanism 57 stirs the liquid in the reaction container with the reagent added thereto.

A pipette probe with a liquid level sensor of the type which is disclosed in U.S. Patent No. 4,451,433 may be used. Fig. 2 illustrates the reagent supply system comprising a combination of the movable reagent containers and the pipetting mechanisms. However, a reagent delivery system comprising a combination of stationary reagent containers and a dispenser mechanism may also be adopted. In Fig. 2, the reaction container 15 on which photometry has been conducted is washed by a washing mechanism 45 before it is supplied for a new sample analysis.

Data reading devices 3A and 3B, each consisting of a bar code reader, are disposed near the reagent disks 16A and 16B shown in Fig. 2 in such a manner that they face the corresponding disks to read the data printed in the form of bar codes. The results of the reading are stored in a storing unit 62 of the control unit 11 correspondingly to the position of each of the reagent containers 1A and 1B on the reagent disks 16A and 16B.

Each of the reagent container accommodating portions includes a reagent container housing unit 7 made of a heat insulating material, and a lid 5 which closes an opening thereof, as shown in Fig. 1. In Fig. 2, illustration of such a reagent container accommodating portion is omitted to simplify the description.

In Fig. 1, the reagent containers 1A each with a bar code label 2 are placed on a movable retainer 16 disposed within the container housing unit 7. The container housing unit 7 has at its upper portion an opening through which the reagent containers are supplied to or discharged from the unit. The opening is normally closed by the lid 5 made

of an insulating material. The lid 5 has a through-hole 58 at a position where it faces the reagent picking position. The pipette probe of the reagent pipetting mechanism 17A enters or leaves the container housing unit 7 through the through-hole 58.

The lid 5 is locked by a shaft 59 in such a manner as to be openable. Opening of the lid lowers a member 19. Thus, when the lid 5 is open, the distal end of the member 19 interrupts the optical path of a photo coupler 4 which is a detector. A resultant interrupt signal is transmitted to the control unit 11. The opened state of the lid 5 is maintained by a spring 20. When the lid 5 is closed, as shown in Fig. 1, the distal end of the member 19 retracts from the photo coupler 4, and the light from a light source in the photo coupler 4 thus reaches a receiving side. The resultant detection signal representing closing of the lid is also transmitted to the control unit 11.

The container housing unit 7 forms a cold reserving unit. This is achieved by disposing a cooling plate 6 on the inner wall thereof. A rotary shaft 70 of the movable retainer 16 has a disk-shaped gear 10 which is in mesh with a gear 9. Thus, a driving force of a stepping motor 8, which is a driving unit controlled by the control unit 11, is transmitted to the disk-shaped gear 10 through the gear 9. Also, a disk-shaped detecting plate 22 is provided on the rotary shaft 70. An angular position of the detecting plate 22 is detected by a position detector 21 which may be a photo coupler. The detection signal is transmitted to the control unit 11. A detecting plate 22 of the type which has detection holes in the disk, disclosed in Japanese Patent Publication No. 1-21910, may be employed. The position of the movable retainer 16 is determined on the basis of detection of the detection hole corresponding to each of the reagent containers. The bar code readers 3A and 3B are mounted on the side wall of the container housing units 7.

The operation of the analyzing apparatus shown in Fig. 2 will be described below.

After the sample containers 52 are placed on the sample disk 13, the operator inputs from the operation panel 64 inspection items designated for each of the samples, and thereby stores the analysis items correspondingly to the sample numbers in the storing unit 62 of the control unit 11. Consequently, the reagents required for each of the analysis items are selected from the reagent table in the storing unit 62, and are separated and registered in first and second reagent registration portions. The registered reagents are stored in the storing unit 62. The reagent registration status is displayed, if the corresponding reagent containers are not placed on the reagent disk 13, on a screen display unit 63 in red. At that time, the first reagents are displayed in a group corresponding to

the first reagent disk 16A, while the second reagents are displayed in a group corresponding to the second reagent disk 16B. If the first reagents are erroneously placed on the second reagent disk 16B, an alarm is issued while such first reagents are displayed in red on the display screen.

Next, the operator opens the lid 5 of each of the first and second reagent container housing units 7 and places the reagent containers 1A and 1B required for measurements of the inspection items on the movable retainer 16 from the opening. When the required number of reagent containers have been placed, the operator closes the lid 5. Closing of the lid 5 allows the opening/closing detector 4 to output the detection signal to the control unit 11. On the basis of the detection signal, the control unit 11 gives the operation starting instruction to the bar code readers 3A and 3B and the corresponding driving units 8. Consequently, each of the movable retainers 16 is intermittently fed one container by one container, while the bar codes of the reagent containers 1A and 1B are read by the bar code readers 3A and 3B when they are temporarily stopped at the positions of the bar code readers 3A and 3B. The reading operation is performed on all of the reagent containers.

Each of the bar code readers 3A and 3B is of the CCD type which optically scans the code inscribed on the container in the vertical direction thereof. Each of the reagent containers stops at the reading portion for 0.5 seconds, during which time the bar code readers 3A and 3B scan the code 50 times.

When the code on all the containers in the container housing unit has been read, the bar code readers 3A and 3B are put in a waiting state. When there is no container at the container loaded site, no code can be read, and the control unit 11 thus determines that there is no container. The bar code data on the reagents is stored in the storing unit 62 correspondingly to the position data on the reagent containers on the movable retainer 16 which have been input from the position detector 21.

The reagent data read for each of the housing units 7 is collated with the previously registered reagent data. If there are reagents which cannot be made to correspond to each other, the type of such a reagent and the position of the reagent container are displayed. If there are first reagents in the second reagent housing unit and vice versa, the control unit 11 locks the reagent delivery system (17A, 17B and 56) and the sample pipetting mechanism 14 and thereby does not start the operation of the analyzing apparatus.

When the operator switches on the analyzing apparatus after the reagents have been placed, if there is no failure on the reagent supply systems, analyzing work begins. However, if there is a failure

on the reagent supply systems, the analyzing apparatus is locked and cannot thus be activated. Thus, the operator notices the failure and can view the alarm data. At that time, the operator calls the reagent data display screen on the display unit 63 from the operation panel 65 and knows at which reagent disagreement is occurring. On the display screen, the type of all the reagents are tabulated in both systems and real names. The reagents on which agreement is obtained are displayed on the screen in blue. The types of reagents on which disagreement is occurring are displayed together with their positions in red.

Thus, the operator replaces the reagent containers within the container housing unit 7 on the basis of the data displayed on the screen. When the operator opens the lid 5 of the housing unit 7, the detector 4 outputs an off signal, and the data already read by the control unit 11 is reset. Even when the reading devices 3A and 3B are operating, opening of the lid 5 resets the reading operation. When the operator replaces the inadequate reagent containers and closes the lid 5, the detector 4 outputs the detection signal, and the reading devices 3A and 3B restart the reading operation of the data on all of the reagent containers. When the reading operation has been performed on all of the containers, the reading devices are put into a waiting state.

Thereafter, the operator calls the reagent data display screen on the screen display unit 63 and checks whether the inadequate reagents have been replaced. When the inadequate reagents have been replaced, all the reagents are displayed in blue on the screen, and the reagent delivery system and the sample pipetting mechanism are unlocked. Thereafter, the operator switches on the analyzing apparatus, which apparatus thereupon initiates the analyzing operation to perform continuous analysis on the samples.

In the analyzing apparatus shown in Fig. 2, a changeover switch is provided which can select one of two modes: the reagent container data reading mode or the reagent level detection mode. When the data reading mode is selected, the data reading operation is performed in the manner described above. In the reagent level detection mode, the remaining amount of a reagent is checked in the following manner.

In the reagent level detection mode, the pipette probes of the reagent pipetting mechanisms 17A and 17B are moved up and down. The pipette probe is washed each time it is used for liquid level detection. When the operator closes the lid 5 after he/she has placed the necessary reagent containers 1A and 1B, the control unit 11 is activated by the output signal of the opening/closing detector 4 to control the driving units 8 and the pipetting

mechanisms 17A and 17B. While the movable re-  
tainer 16 is intermittently rotated within the housing  
unit 7, the position detector 21 checks the position  
of each of the containers. During the intermittent  
operation of the movable retainer 16, the pipette  
probe falls through the through-hole 58 toward the  
reagent container and then touches the level of the  
reagent in the container 1.

Since the pipette probe has a reagent level  
detecting unit, when it touches the liquid surface, it  
stops falling, and outputs an on signal. The remain-  
ing amount of reagent contained in the relevant  
container is calculated using the liquid height data  
from the bottom of the reagent container 1 and the  
size of the container, and how many more samples  
can be inspected with the remaining amount is  
calculated. After liquid level detection has been  
conducted on a certain container, the pipette probe  
is raised and then the liquid level in a container  
moved under the through-hole 58 by a subsequent  
step feed is detected.

When liquid level detection has been made on  
all the reagent containers, the analyzing apparatus  
is put in a waiting mode. The results of liquid level  
detection can be displayed on the screen display  
unit 63. The instruction of the display is given from  
the operation panel 65. It may be programmed  
such that liquid level detection is performed imme-  
diately after data reading.

Another embodiment of the present invention  
will be described below with reference to Figs. 3  
and 4. In these figures, the same reference char-  
acters are used to denote parts which have the  
same functions as those of the first embodiment.  
Fig. 3 schematically illustrates an analyzing appara-  
tus. Fig. 4 illustrates a reagent container housing  
unit of the analyzing apparatus.

In the analyzing apparatus shown in Figs. 3  
and 4, a reagent container housing unit 77 dis-  
posed in the reagent container accommodating  
portion is made fixed such that it does not move  
the first reagent containers 1A and the second  
reagent containers 1B. Reagent pipetting mecha-  
nisms 76A and 76B for the corresponding reagent  
systems can be stopped in such a manner that  
they can face each of the containers and can be  
moved over the reagent container rows. The  
reagent selectively picked from the containers 1A  
and 1B is delivered to the reaction container on the  
reaction disk 50 by a pipette probe 74. The hous-  
ing unit 77 has a light transmission window 23. A  
bar code reader 73 reads through the window 23  
the data on the reagent which is printed on a bar  
code label 2 adhered to each of the reagent con-  
tainers 1.

The bar code reader 73 is mounted on a mov-  
able member of the reagent pipetting mechanism  
76. To read the bar code, the movable member is

moved in the lateral direction, i.e., along the row of  
the containers, so that the bar codes on all the  
reagent containers can be read. A lid 75 is pro-  
vided on the housing unit 77 in such a manner that  
it can be opened and closed. When the reagent  
containers are placed in or removed from the hous-  
ing unit 77, the lid 75 is opened. After the reagent  
containers have been placed, the lid 75 is closed.  
When closing of the lid 75 is detected by the  
opening/closing detector 4, the reading operation of  
the bar code reader 73 begins.

As will be understood from the foregoing de-  
scription, in the present invention, the operator can  
reliably grasp the data on the liquid contained in  
each of the containers by closing the lid of the  
container housing unit after he/she has placed the  
containers therein. As a result, newest data can be  
obtained without errors even when the containers in  
the container housing unit are replaced.

Furthermore, since the analyzing apparatus  
automatically makes collation, a trouble caused by  
inadequate reagent placed on the incorrect reagent  
position can be prevented.

## Claims

1. An automatic analyzing apparatus including a  
container housing unit having an opening  
through which a container with data on a liquid  
contained therein inscribed thereon is loaded,  
and a reading device for reading the data of  
the container loaded in said container housing  
unit, said apparatus comprising:  
a lid for covering the opening;  
a signal output unit for outputting a signal  
when the opening has been closed by said lid;  
a control unit for starting the data reading  
operation by said reading device on the basis  
of the output of the signal.
2. An automatic analyzing apparatus according to  
claim 1, wherein opening of said lid erases the  
already read data.
3. An automatic analyzing apparatus according to  
claim 1, wherein when the data reading opera-  
tion is performed, a row of containers placed in  
said container housing unit and said reading  
device are moved relative to each other, during  
which time the data inscribed on the containers  
are read by said reading device in sequence.
4. An automatic analyzing apparatus according to  
claim 3, wherein said container housing unit  
has container conveying means for moving the  
row of container intermittently during the data  
reading operation.

5. An automatic analyzing apparatus according to claim 1, further comprising a liquid delivery device having a pipette probe having a liquid level sensor, said liquid delivery device detecting a level of the liquid in the container while said lid is being closed. 5
6. An automatic analyzing apparatus according to claim 5, further comprising selection means for selection one of a data reading mode performed by said reading device and a liquid level detection mode performed by said liquid delivery device. 10
7. An automatic analyzing apparatus according to claim 5, further comprising a registration unit in which data on types of reagents in the reagent containers which are to be housed in said container housing unit are registered beforehand, and wherein said control unit stops the operation of said liquid delivery device when the type of the reagent obtained on the basis of the inscribed data does not correspond to any of the types of reagents which have been registered. 15 20 25
8. An automatic analyzing apparatus according to claim 5, wherein during the liquid level detection, the row of containers placed in said container housing unit and said pipette probe are moved relative to each other. 30
9. A reagent handling method for reading data inscribed on a reagent container loaded in a container housing unit by a reading device, said method comprising the steps of; 35
  - outputting a signal when a lid of said container housing unit has been closed; and
  - starting a data reading operation of said reading device on the basis of the signal. 40
10. A reagent handling method according to claim 9, wherein while said lid is being closed, a liquid delivery device having a liquid level sensor is activated to detect a level of the liquid in the reagent container. 45
11. A reagent handling method according to claim 10, wherein when a type of reagent which is read by said reading device does not correspond to any of types of reagents which are expected, said liquid delivery device does not start the reagent delivery operation. 50
12. A reagent handling method according to claim 9, wherein opening of said lid erases the data which has been already read. 55
13. A reagent handling method according to claim 9, wherein when the data on the plurality of reagent containers are read by said reading device and either of the reagents which have been read does not correspond to types of reagents which have been registered beforehand, the disagreeing reagent is displayed on a display device.
14. A reagent handling method according to claim 13, wherein said display device is a screen display device which can perform display in a plurality of colors, the reagents which correspond to the registered data being displayed on the screen in a color different from that in which the reagents which do not correspond to the registered data are displayed on the screen.

FIG. 1






FIG. 2




FIG. 3





FIG. 4





Europäisches Patentamt  
European Patent Office  
Office européen des brevets



Publication number: **0 510 686 A3**

(12)

## EUROPEAN PATENT APPLICATION

(21) Application number: **92107052.0**

(51) Int. Cl.<sup>5</sup>: **G01N 35/02, G01N 33/48,  
G06K 7/10, G05B 15/00**

(22) Date of filing: **24.04.92**

(30) Priority: **26.04.91 JP 96721/91**

(43) Date of publication of application:  
**28.10.92 Bulletin 92/44**

(64) Designated Contracting States:  
**DE FR GB**

(88) Date of deferred publication of the search report:  
**24.02.93 Bulletin 93/08**

(71) Applicant: **HITACHI, LTD.**  
**6, Kanda Surugadai 4-chome**  
**Chiyoda-ku, Tokyo 101(JP)**


(72) Inventor: **Takahashi, Katsuaki**  
**2031-813, Tsuda**  
**Katsuta-shi(JP)**  
Inventor: **Mitsumaki, Hiroshi**  
**2819-17, Senbacho**  
**Mito-shi(JP)**  
Inventor: **Yotsugi, Takehiko**  
**Nakagawa Apato E-104, 1030, Ichige**  
**Katsuta-shi(JP)**

(74) Representative: **Altenburg, Udo, Dipl.-Phys. et**  
**al**  
**Patent- und Rechtsanwälte**  
**Bardehle-Pagenberg-Dost-Altenburg**  
**Frohwitter-Geissler & Partner Postfach 86 06**  
**20**  
**W-8000 München 86 (DE)**

(54) **Automatic analyzing apparatus capable of reading container data and method of handling reagents employed in the same.**

(57) When a lid (5) of a reagent container housing unit (7) is closed, an opening/closing detector (4) outputs a signal. A control unit (11) gives an instruction of moving a row of reagent containers (1) and a bar code reader (3) relative to each other to a driving unit and an instruction of starting the data reading operation to the bar code reader (3). When the lid (5) of the container housing unit is closed, all the data which have been already read are reset. An automatic analyzing apparatus can select, in place of the data reading mode, the liquid level detection mode in which a level of the liquid in each of the reagent containers is detected.

FIG. 1



EP 0 510 686 A3



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number

EP 92 10 7052

Page 1

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
A	CLINICAL CHEMISTRY vol. 34, no. 9, September 1988, WASHINGTON DC, US pages 1726 - 1732 M. FIORE ET AL. 'The Abbott IMx automated benchtop immunochemistry analyser system' * page 1727, left column, line 3 - line 25 * * page 1727, right column, line 24 - line 26 *	1-3,9,12	G01N35/02 G01N33/48 G06K7/10 G05B15/00
A	EP-A-0 192 968 (FISHER SCIENTIFIC COMPANY) * page 12, line 7 - line 30 *	1-3,9,12	
A,D	US-A-4 451 433 (K. YAMASHITA ET AL.) * column 6, line 13 - column 9, line 40 *	1,5, 8-10,14	
A	PATENT ABSTRACTS OF JAPAN vol. 13, no. 469 (M-883)24 October 1989 & JP-A-11 84 184 ( VICTOR CO OF JAPAN LTD ) 21 July 1989 * abstract *	1,2,9,12	
A	GB-A-2 131 168 (JAPAN TECTRON INSTRUMENTS CORP.) * page 4, line 70 - page 6, line 7; figures 5-9 *	1,5,9,10	
D	& JP-A-59 226 865 (IDEM)		
A	PATENT ABSTRACTS OF JAPAN vol. 8, no. 141 (P-283)(1578) 30 June 1984 & JP-A-59 40 167 ( SHIMAZU SEISAKUSHU K.K. ) 5 March 1984 * abstract *	1,9	
A	GB-A-2 216 259 (MICROVOL LTD)		
A	EP-A-0 359 049 (HITACHI LTD.)		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 09 DECEMBER 1992	Examiner HODSON C.M.
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			
T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... & : member of the same patent family, corresponding document			



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number

EP 92 10 7052

Page 2

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
A	PATENT ABSTRACTS OF JAPAN vol. 10, no. 264 (P-495)9 September 1986 & JP-A-61 088 234 ( CANON INC. ) 6 May 1986 * abstract *  -----		
			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
The present search report has been drawn up for all claims			
Place of search	Date of completion of the search	Examiner	
THE HAGUE	09 DECEMBER 1992	HODSON C.M.	
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			
T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... Δ : member of the same patent family, corresponding document			